


Experienced and Reliable!

D465B 4in Desktop Label Printer

- ✓ 152 mm (6") / s Max. high speed print speed
- ✓ Low noise, High speed printing
- ✓ 8MB SDRAM, 8 MB Flash
- ✓ 203 dpi resolution models
- ✓ High quality double-walled clamshell design
- ✓ TSPL, EPL, ZPL, DPL



APPLICATION



Supermrket



Medical Care



Storage



Post



Catering



Store



D465B Specification

Printing Features	
Resolution	203 DPI
Printing method	Direct Thermal
Max.print speed	152 mm (6") / s Max.
Max.print width	108 mm (4.25")
Max.print length	1778 mm
Media	
Media type	Continuous, gap, black mark, fan-fold and punched hole
Media width	26 mm ~ 118 mm
Media thickness	0.06~0.254 mm (2.36~10mil)
Media core diameter	25.4 ~ 76.2 mm (1"~ 3")
Label length	10 mm ~1778 mm
Performance Features	
Processor	32-bit CPU
Memory	8MB Flash Memory, 8MB SDRAM
Interface	Standard version: USB 2.0 Optional:WIFI/Bluetooth
Sensors	Gap sensor,Cover opening sensor,Black mark sensor,paper exit sensor
Fonts/Graphics/Symbologies	
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D bar code	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13,EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on,MSI, PLESSEY, POSTNET, China POST
2D bar code	PDF-417, Maxicode, DataMatrix, QR code, Aztec
Rotation	0°,90°,180°,270°
Emulaion	TSPL,EPL,ZPL,DPL
Physical Features	
Dimension	185 mm (L) x 85 mm (W) x 85 mm (H)
Weight	732g
Power	Input:AC 100-240V Output:DC 24V, 2.5A
Software	
Driver	Windows/ Linux/ Mac
SDK	Windows/ Android/ iOS
Options	
Factory Options	Peeler,Cutter ,RTC
Dealer Options	External paper roll holder Paper roll spindle Extension board for external paper roll holder
Environmental Conditions	
Operation environment	5 ~ 40°C(41~104°F),Humidity: 25 ~ 85% no condensing
Storage environment	-40 ~ 60°C(-40~140°F),Humidity: 10 ~ 90% no condensing