

P322B

Mobile Label printer



Key features

- Support direct USB charging;
- Long lasting battery life;
- Dual mode bluetooth;
- OLED screen available;
- TSPL, EPL, ZPL, DPL, CPCL, ESC/POS command compatible.

Applications



Shopping



Mart



Restaurant



Hospital




Coffee Shop



Ticketing

P322B

Mobile Label Printer



Printing		P322B	
Resolution	203 DPI		
Printing method	Direct Thermal		
Max.print speed	Max. 70mm (2.7") / s		
Max.print width	72 mm (2.8")		
Max.print length	1778 mm (70")		
Media			
Media type	Continuous, gap, black mark		
Media width	25.4 mm ~ 76 mm		
Media thickness	0.06 mm ~0.254 mm		
Label roll diameter	50mm		
Performance Features			
Processor	32-bit CPU		
Memory	8MB Flash Memory/ 8MB SDRAM		
Interface	Stardard version: USB+Bluetooth Optional:USB+WIFI		
Screen	OLED (0.96 ") Resolution:128*64 pix		
Sensors	①Gap sensor ②Cover opening sensor ③Black mark sensor		
Fonts/Graphics/Symbologies			
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software		
1D bar code	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on,MSI, PLESSEY, POSTNET, China POST		
2D bar code	PDF-417, Maxicode, DataMatrix, QR code,Aztec		
Rotation	0°、 90°、 180°、 270°		
Emulaion	TSPL、 EPL、 ZPL、 DPL、 CPCL、 ESC/POS		
Physical Features			
Dimensions	120×112×60 mm (D×W×H)		
Weight	400 g		
Reliability			
Printer head llfe	30Km		
Software			
Operation system	Windows / Android / iOS		
SDK	Windows / Android / iOS		
Power supply			
Adapter	Input:AC 100-240V,0.5A, 50-60Hz Output: DC 5V/2A		
Battery	2500mAh		
Environmental Conditions			
Operation environment	5 ~ 40°C (41~104°F) , Humidity: 25 ~ 85% no condensing		
Storage environment	-40 ~ 60°C (-40~140°F) , Humidity: 10 ~ 90% no condensing		